

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A docking station for a wireless communication device, the docking station comprising:

a support structure;

a cradle situated in the support structure to receive the wireless communication device;

a display situated in the support structure to display information received by the docking station from the wireless communications device; and

an energy source internal to the docking station which supplies energy to the docking station and to a rechargeable energy source in the wireless communication device when the wireless communication device is received in the cradle and which supplies energy to the wireless device when the docking station is mobile.

2. (Currently Amended) A docking station for a wireless communication device, the docking station comprising:

a docking housing;

a display device, situated in the docking housing, that displays information received from the wireless communication device;

a cradle, disposed on the docking housing, that receives the wireless communication device;

a connector, situated in the cradle, that electrically couples the docking station to the wireless communication device; and

~~an internal voltage source situated in the docking housing;~~

~~a charging circuit, situated in the docking housing, for charging a voltage source;~~

and  
~~a switch for selectively coupling the charging circuit to the internal voltage source.~~  
an energy source internal to the docking station which supplies energy to the docking station and to a rechargeable energy source in the wireless communications device when the wireless communications device is received in the cradle and which supplies energy to the wireless device when the docking station is mobile.

3. (Currently Amended) A docking station for a wireless communication device as defined in Claim 2, wherein the connector comprises a first terminal coupled to the internal-voltage energy source.

4. (Currently Amended) A docking station for a wireless communication device as defined in Claim 3, wherein the connector comprises a second terminal selectively coupled to ~~the~~ a charging circuit through the switch in the docking housing via a switch.

5. (Original) A docking station for a wireless communication device as defined in Claim 4, wherein the connector comprises a third terminal coupled to GND.

6. (Cancelled).

7. (Original) A docking station for a wireless communication device as defined in Claim 4, wherein the switch has a pole coupled to the charging circuit and has a first terminal selectively coupled to the first terminal of the connector.

8. (Previously Presented) A docking station for a wireless communications device as defined in Claim 7, wherein the switch has a second terminal selectively coupled to

the second terminal of the connector.

9. (Cancelled).

10. (Cancelled).

11. (Cancelled).

12. (Cancelled).

13. (Cancelled).

14. (Cancelled).

15. (Cancelled).

16. (Cancelled).

17. (Currently Amended) A docking station for a wireless communication device as defined in Claim ~~16~~ 2, further comprising a video interface coupled to the display device and operable to transform a video signal generated by the wireless communication device into a video signal that is compatible with the display device.

18. (Currently Amended) A docking station for a wireless communications device comprising:

a display device that displays information received from the communications device; and

a cradle in the docking station that receives the communications device; and

an apparatus that selectively supplies power to the communications device, the apparatus including:

a connector for electrically coupling the docking station to the communications device, the connector having at least first and second terminals;

a switch having a pole, a first terminal, and a second terminal, the switch operable in response to status information indicating whether a the communications device is docked at the docking station;

a charging circuit coupled to the pole of the switch;

~~a station power source coupled to the first terminal of the switch; and~~

a detector that determines whether a the communications device is docked at the station and provides status information as a result of the determination; and

an energy source internal to the docking station which supplies energy to the docking station and to a rechargeable energy source in the wireless communications device when the wireless communications device is received in the cradle and which supplies energy to the wireless device when the docking station is mobile.

19. (Previously Presented) A docking station as defined in Claim 18, wherein the first terminal of the switch is electrically coupled to the first terminal of the connector and the second terminal of the switch is electrically connected to the second terminal of the connector.

20. (Currently Amended) A docking station as defined in Claim 19, wherein the switch operates to connect the pole terminal to the first terminal in response to status information indicating that a the communications device is not docked at the docking station, whereby the charging circuit then charges the ~~station power~~ internal energy source.

21. (Cancelled).

22. (Currently Amended) A method of enhancing the capabilities of a wireless communications device for information handling, the method comprising:

mounting the wireless communications device on a docking station that comprises:

- (a) a cradle for the wireless communications device,
  - (b) a display device that displays information received from the wireless communications device,
  - (c) a connector for effecting an electrical interface to the wireless communication device,
  - (d) ~~a station power source,~~ an energy source internal to the docking station which supplies energy to the docking station and to a rechargeable energy source in the wireless communications device when the wireless communications device is received in the cradle and which supplies energy to the wireless device when the docking station is mobile;
  - (e) a charging circuit, and
  - (f) a switch operable in response to information indicating whether or not a wireless communications device is docked at the docking station;
- coupling a video output from the wireless communications device to the display device;
- causing the station power source to be coupled to the wireless communications device; and
- causing, in response to information that the wireless communication device is docked at the station, the charging circuit to charge the wireless communications device.

23. (Currently Amended) A method as defined in Claim 22, wherein, in response to information indicating that a wireless communications device is docked at the docking station, the switch couples the charging circuit to ~~a voltage~~ the rechargeable energy source included with the wireless communications device, and in response to information indicating that a wireless communications device is not docked at the station, the switch couples the charging circuit to ~~the station power~~ energy source internal to the docking station.
24. (Currently Amended) An assembly for docking a wireless communication device (WCD) so as to enhance the capabilities of the device, the assembly comprising:  
a housing having a receptacle for the WCD;  
a display device that displays information received from the WCD;  
~~an internal chargeable power source;~~ an energy source internal to the docking station which supplies energy to the docking station and to a rechargeable energy source in the wireless communications device when the wireless communications device is received in the cradle and which supplies energy to the wireless device when the docking station is mobile;  
a charging circuit;  
a switching circuit, responsive to a predetermined status of the assembly, that selectively couples the charging circuit to the ~~internal chargeable~~ energy power source;  
~~detachable means for coupling the charging circuit to a source of electrical power;~~  
a video interface circuit for coupling the video output of the WCD to the display device;  
a connector for electrically coupling the docking station to the WCD; and  
a support for the housing.

25. (Previously Presented) An assembly as defined in Claim 24, wherein the display device is mounted on a planar surface of the housing.
26. (Original) An assembly as defined in Claim 25, wherein the support for the housing is a stand having a base portion and an oblique back portion.
27. (Original) An assembly as defined in Claim 25, wherein the support is rotatably attached to the housing.
28. (Cancelled).
29. (Cancelled).
30. (Cancelled).
31. (Cancelled).
32. (Cancelled).